


## IPM-620



- Customizable Screen
- 8 VoIP accounts
- VoIP+PSTN
- Adjustable bracket
- HD Voice: HD Codec
- BLF, XML Phonebook
- Headset, PoE, 2xRJ45
- 6 Expansion Modules

IPM-620 represents the next-generation 8-line SIP phone that feature large HD graphic LCD display, 4 dynamic context-sensitive soft keys, dual 10/100Mbps auto-sensing Ethernet ports with integrated PoE. The IPM-620 series offer excellent voice clarity, comprehensive telephony features, automated provisioning, security protection for privacy. It is a powerful IP telephone for advanced enterprise users.

Function Keys	4 soft keys, 8 Line keys 6 Navigation keys (Arrow button, OK button, C button) Volume adjust, Hands-free, Mute, Headset, Message, Menu Directory, Service, Hold, Redial, Conference, Transfer
VoIP Protocol	SIP 2.0
Network Protocol	HTTP, BOOTP, FTP, TFTP, IEEE 802.1Q, IEEE 802.1X
Codec	G.723.1, G.729 A/B, G.711 A/U, G.722
QoS	TOS, Jitter Buffer, VAD, CNG, G.168 (32ms)
Network	2xRJ45 10/100M Ethernet Interfaces (LAN/PC) IP Assignment: static IP or DHCP DNS Client
Speech	Handset, Headset and Hands-free mode available Support call centre headsets and PC headsets Separated 8 Level Volume Adjustment
Call Processing	Line Status Indicator Multi Account Call Waiting, Call Queuing, Line Switching Call Forward, Call Transfer, Call Holding, Call Pickup, Callback One Key Dial, Redial Phone directory speed dial, call record direct dial 3-way conference DnD, Blacklist Voice mail, Voice Prompt, Voice Message BLF
Expansion Interface	EXT: ESM32 programmable Key module SOR: FXS, FXO, Record USB
Application	Public phone directory Private phone directory PnP (Plug&Play) Photograph album XML Used as intellectual terminals
Security	Login the website by password Signaling encryption Media encryption
Management	Upgrade: HTTP/TFTP/PnP auto-provision Configurations: Phone/Web/auto-provision Debug: Telnet/Phone/Web
Power Supply	Power adapter: AC100~240V input and DC 12V/1A output PoE (IEEE 802.3af)
Specifications	Storage Temperature: 0°C ~ 60°C Operating Humidity: 10%~90% Size: 254mm*205mm*87mm Net weight: 0.9kg



Your Route to The Destination